



DoP

## Declaration of performance

N°ATI-MF01-001-0818



13984:2013

# MF 01

1. Unique identification of the product-type:  
**ATI MF 01**
2. Type : batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) :  
**ATI MF 01**  
Production date : see product or packaging.
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Flexible sheets for waterproofing. Plastic and rubber vapour control layers.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
**ATI France** - 146 Avenue du Bicentenaire - 01120 DAGNEUX - France
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
Not applicable.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
3, 4
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**TSUS – notified body n° 1301**  
has carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
Not applicable.

## 9. Declared performance:

| Characteristics   | Performances   | Standards     |
|---|--|---------------|
| Reaction to fire  | Euroclasse F   | EN 13984:2013 |
| Water tightness   | Watertight at 2 kPa  |               |
| Water vapour resistance   | $37.10^9 \pm 9.10^9 \text{ m}^2 \cdot \text{sPa/kg}$<br>$\mu$ 287<br>Sd 7,18 m |               |
| Durability <ul style="list-style-type: none"> <li>Against ageing</li> <li>Against alkali</li> </ul> | Pass<br>NPD *  |               |
| Resistance to tearing by nail shank   | LD: min. 190 N<br>TD: min. 200 N   |               |
| Tensile properties:   | LD: min. 260 N/50 mm<br>TD: min. 310 N/50 mm                                   |               |
| - Maximum tensile force and elongation  | LD: min. 8 %<br>TD: min. 9 %   |               |
| Resistance to impact  | NPD *  |               |
| Joint strength  | NPD *  |               |

\* Undetermined performance

## 10. Dangerous substances:

None

## 11. Characteristics (excluding CE Mark)

Class of emissions of volatile substances into indoor air (VOC):

**A+**

12. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sophie Galichet  
Sales manager

Dagneux, le 24/08/2018

